



Features and Benefits

- Complies with all requirements of ISO 21501-4
- 0.3 to 25 μm size range
- 2.83 L/min (0.1 CFM) flow rate
- Measures up to six channels of simultaneous data
- Model 9306-V2 provides unique variable binning option
- Integrated handle for one hand operation
- Removable, rechargeable Li-ion battery
- Long life laser diode
- USB and Ethernet output
- 10,000 sample record storage, 250 locations
- Local or remote configuration via web browser
- Provides Pass/Fail reporting on ISO 14644-1, EU GMP, and FS209E
- Compatible with TRAKPRO™ Lite and FMS 5 software packages
- Optional Temperature/RH sensor available

AEROtrak™ Handheld Particle Counter Model 9306

The TSI AEROtrak™ 9306 Handheld Particle Counter offers the most features and flexibility for customers interested in versatile handheld particle contamination monitoring. The Model 9306 features an ergonomic handle with thumb controls, for easy one-hand operation. The 9.1-cm color touch screen interface makes it easy to configure and operate. The Model 9306 can generate Pass/Fail reports for ISO 14644-1, EU GMP Annex 1, and FS209E. The internal memory can store up to 10,000 sample records of particle count data which can be conveniently viewed on screen, downloaded using TrakPro™ Lite Software, or printed directly to an optional external printer.

The Model 9306 complies with all the stringent requirements set forth in ISO 21501-4. These particle counters are calibrated with NIST traceable PSL spheres using TSI's world-class Classifier and Condensation Particle Counters, the recognized standard for particle measurements. Backed with a standard two-year warranty and TSI's long-standing reputation for high quality, there are no other handheld particle counters like it on the market today.



Specifications

Model 9306

AERO^{TRAK}™ Handheld Particle Counter

Features	9306
Size Range	0.3 to 25 µm
Particle Channel Sizes	9306-03: 0.3, 0.5, 0.7, 1.0, 2.0, 5.0 µm 9306-04: 0.3, 0.5, 1.0, 3.0, 5.0, 10.0 µm 9306-V2: 0.3 to 10 µm, user-selectable; factory-calibrated at 0.3, 0.5, 1.0, 3.0, 5.0, 10.0 µm
Size Resolution	<15% @ 0.5 µm (per ISO 21501-4 requirements)
Counting Efficiency	50% at 0.3 µm; 100% for particles >0.45 µm (per ISO 21501-4 and JIS)
Concentration Limit	>2,000,000 particles/ft ³ at 5% coincidence loss
Light Source	Long life laser diode
Zero Count	<1 count per 5 minutes (per ISO 21501-4 and JIS B9921)
Flow Rate	2.83 L/min (0.1 CFM) with ±5% accuracy (meets ISO 21501-4 and JIS requirements)
Flow Rate Control	Electronic, automatic closed loop (patented* flow control technology)
Calibration	NIST Traceable with TSI calibration system
Calibration Frequency	Recommended minimum once per year
Sampling Modes	Manual, automatic, beep; cumulative/differential; count or concentration
Sampling Time	1 second to 99 hours
Sampling Frequency	1 to 9999 cycles or continuous
Exhaust	Internally filtered
Communication Mode	Modbus [®] RTU over Ethernet or USB
Data Storage	10,000 sample records: includes date, time, six particle channels, flow, ID, and sample volume; transferable via USB data download or TRAK ^{PRO} ™ Lite software
Alarm Status	Audible alarm on counts
Status Indicators	Low battery, flow, laser
Environmental Sensors	Optional Temp/RH probe
Display	QVGA 9.1-cm touch screen
Reports	Provides Pass/Fail on ISO 14644-1, EU GMP, and FS209E reports

Features	9306
Unit ID	Configurable IP address
Security	2-level password protection to lock out usage and configuration
Location ID	Up to 999 Locations; 16 characters long
Languages	English, Japanese, German, French, Spanish, and Chinese (simplified), Italian
Software	Compatible with TRAK ^{PRO} ™ Lite and FMS 5 Software
External Surface	High Impact injection molded plastic
Dimension (H x W x D)	23.9 cm x 11.7 cm x 12.4 cm (without isokinetic inlet, includes handle)
Weight	1.0 kg with battery
Power	110 to 240 VAC, 50 to 60 Hz universal in-line power supply
Battery	Removeable/rechargeable Li-Ion
Battery Life	>6 hours of continuous use
Recharge Time	<2 hours
Standards	ISO 21501-4, CE, JIS B9921
Warranty	Two years, extended warranties available
Operating Range	5° to 35°C, 20% to 95% noncondensing
Storage Range	0° to 50°C, up to 98% RH noncondensing
Included Accessories	Operating manual on CD, power supply, battery, isokinetic inlet, purge filter, stylus, USB cable and TRAK ^{PRO} ™ Lite software
Optional Accessories	Spare Battery, external battery charger, isokinetic probe, sample tubing, Temp/RH probe, printer, printer paper and carrying case

Patent Number 6,167,107

Specifications are subject to change without notice. TSI, the TSI logo, AERO^{TRAK}, and TRAK^{PRO} are trademarks of TSI Incorporated. Modbus is a registered trademark of Modicon, Inc.

TSI Incorporated - 500 Cardigan Road, Shoreview, MN 55126-3996 USA

USA	Tel: +1 800 874 2811	E-mail: info@tsi.com	Website: www.tsi.com
UK	Tel: +44 149 4 459200	E-mail: tsiuk@tsi.com	Website: www.tsiinc.co.uk
France	Tel: +33 491 11 87 64	E-mail: tsifrance@tsi.com	Website: www.tsiinc.fr
Germany	Tel: +49 241 523030	E-mail: tsigmbh@tsi.com	Website: www.tsiinc.de
India	Tel: +91 80 41132470	E-mail: tsi-india@tsi.com	
China	Tel: +86 10 8260 1595	E-mail: tsibeijing@tsi.com	
Singapore	Tel: +65 6595 6388	E-mail: tsi-singapore@tsi.com	



TRUST. SCIENCE. INNOVATION.

Contact your local TSI Distributor or visit our website www.tsi.com for more detailed specifications.